



INLINE SERIES - 4000 HEATED 1200mm SQUARE FREESTANDING

MODELS

- IN-4H12-SQ-FF-FS | 4000 Series heated 1200mm square freestanding, with fixed front glass
- IN-4H12-SQ-SD-FS | 4000 Series heated 1200mm square freestanding, with sliding glass doors

OPTIONS [F=Factory Fitted]

- Lockable castors (F)
- Rear door mirror application (F)
- End glass mirror application (F)

ACCESSORIES [A=Accessory]

- Small goods tray (A)
- Angled base shelf (A)
- Thermal divider panels (A)
- Pie chutes and dividers (A)
- Wire shelves (A)
- Chicken trays (A)
- Rear decks (A)
- Stainless steel flat trays (A)

OVERVIEW

Inline 4000 Series food and drink display cabinets are ideal for the busy food service business wanting to display a large quantity or wide variety of food. This Cabinet Series is tested to 85 door openings an hour while still maintaining core product temperatures for food safety. The lighting and merchandising features are designed to create impact and increase sales. A plug and go solution, **Inline 4000 Series** cabinets are quick and easy to install with a range of installation options available: in counter, on counter, and freestanding. Developed using FPG's world class design expertise to extend shelf life and help you sell more. Optimised for energy efficiency and to deliver the lowest total cost of ownership over the life of the cabinet. A proven high capacity cabinet.

FEATURES

- High energy efficiency - 1.72 kWh per hour average
- Cabinet operating temperature range +30°C - +90°C
- Recommended core product temperature > +65°C
- Sliding doors (staff side) and fixed front or sliding doors options (customer side)
- Three adjustable shelves and base for product display
- 25,000 hour LED lighting to cabinet top and shelves
- Low wattage high density elements for even temperature distribution
- Fascia and base extrusions can be fitted with clip-in decorative inserts
- Adjustable 150mm feet (+30mm adjustment)
- Unique shelf mounted ticket strip to front and rear
- Toughened safety glass
- Also available as in counter or on counter models



SHOWING : 4000 SERIES HEATED 1200mm SQUARE FREESTANDING, WITH FIXED FRONT

IN-4H12-SQ-FF-FS	ENVIRONMENTAL TEST CONDITIONS	22°C / 65% RH	MAX TEMPERATURE RANGE	+30°C-+90°C
IN-4H12-SQ-SD-FS				

FPG heated food display cabinets are designed to meet and exceed:

- International safety standards for electrical heated appliances: IEC 60335-1, IEC 60335-2-49, IEC 60335-2-50, and the equivalent country-specific standards including AS/NZS and BS EN.
- International standards for electromagnetic compatibility/emissions: CISPR 14-1, and the equivalent county-specific standards including AS/NZS CISPR and BS EN 55014-1.
- Essential safety requirements: AS/NZS 3820 and AS/NZS 4417.

Please contact FPG to discuss your requirements for meeting country-specific standards.



FPGWORLD.COM



INLINE SERIES - 4000 HEATED 1200mm SQUARE FREESTANDING

SPECIFICATIONS

Heated Data

	ENVIRONMENTAL TEST CONDITIONS	RECOMMENDED CORE PRODUCT TEMP	MAX TEMP RANGE	HEATING
IN-4H12-SQ-FF-FS	22°C / 65% RH	> +65°C	+30°C - +90°C	High density low wattage element
IN-4H12-SQ-SD-FS	22°C / 65% RH	> +65°C	+30°C - +90°C	High density low wattage element

Electrical Data

	VOLTAGE	PHASE	CURRENT	kWh per hour [average]	MAINS CONNECTION	MAINS CONNECTION PLUG	IP RATING	LED LIGHTING
IN-4H12-SQ-FF-FS	220-240 V	Single	7.1 A	1.72 kWh per hour	3 metre 3 core cable	10 amp, 3 pin plug	IP 20	25,000 hr LED
IN-4H12-SQ-SD-FS	220-240 V	Single	7.1 A	1.72 kWh per hour	3 metre 3 core cable	10 amp, 3 pin plug	IP 20	25,000 hr LED

Display

	DISPLAY AREA	NO. OF SHELVES	ACCESS - FRONT	ACCESS - REAR	CONSTRUCTION
IN-4H12-SQ-FF-FS	2.1m ²	3 + Base	Fixed front	Sliding doors	304 Stainless Steel
IN-4H12-SQ-SD-FS	2.1m ²	3 + Base	Sliding doors	Sliding doors	304 Stainless Steel

Dimensions [Uncrated and Crated]

	H x W x D mm [Uncrated]	MASS [Uncrated]	H x W x D mm [Crated]	MASS [Crated]	CUBIC VOLUME [Crated]
IN-4H12-SQ-FF-FS	1405 x 1203 x 778	170 kg	1595 x 1285 x 935	270 kg	1.92m ³
IN-4H12-SQ-SD-FS	1405 x 1203 x 778	170 kg	1595 x 1285 x 935	270 kg	1.92m ³

In line with policy to continually develop and improve it's products, Future Products Group reserves the right to change specifications and design without notice.

For more information and technical data, including installation documents, please refer to the website - www.fpgworld.com

